

## Robulon PP

### Technical Data

TenCate Geolon® Robulon PP is a high strength geocomposite for erosion control purposes. The product is made of 100% highly durable and UV resistant PP, with a 3 dimensional structure. The combination of reinforcement and soil retention makes Robulon the ideal mat for erosion control in a variety of applications such as protection of slopes, geomembranes, canal and river beddings, and shorelines.



TenCate Geolon® Robulon PP

Characteristics <small>(Standard)</small>	Unit	PP 40	PP 60	PP 80	
<b>Type of product</b>		Geocomposite made of 100% polypropylene, consisting of a high strength woven base layer featuring inseparable loops for soil, gravel or concrete retention			
<b>Product Properties</b>					
Mass per unit area <small>[EN ISO 9864]</small>	g/m <sup>2</sup>	510	580	675	
Thickness under 2kPa <small>[EN ISO 9863-1]</small>	mm	10	10	10	
UV resistance (retained tensile strength) <small>[EN ISO 12224]</small>	%	> 80	> 80	> 80	
<b>Base Layer Properties</b>					
Tensile strength <small>[EN ISO 10319]</small>	MD*	kN/m	40	63	84
	CD*	kN/m	40	57	84
Elongation at maximum strength <small>[EN ISO 10319]</small>	MD*	%	17	8	8
	CD*	%	12	8	8
CBR puncture resistance <small>[EN ISO 12236]</small>		kN	4	6	8
Dynamic perforation <small>[EN ISO 13433]</small>		mm	15	10	9
<b>Forms of supply</b>					
Width	m	5	5	5	
Length	m	45 / 50	50	50	
Roll diameter	m	0.78 / 0.8	0.85	0.85	
Roll weight <small>(indicative)</small>	kg	125 / 140	160	180	

\* MD = Machine Direction CD = Cross Direction

The values given are average values obtained in our laboratories and in testing institutes. The right is reserved to make changes without notice at any time..

#### TENCATE GEOSYNTHETICS AUSTRIA GMBH

Schachermayerstr. 18  
A-4021 Linz, Austria  
Tel. + 43 732 6983 0, Fax + 43 732 6983 5353  
service.at@tencategeo.com, www.tencategeo.at

**BeNeLux**  
**Central Eastern Europe**  
**Czech Republic**  
**France | Africa**  
**Germany**  
**Italy**  
**Near Middle East**

Tel. + 31 546 544 811  
Tel. + 43 732 6983 0  
Tel. + 420 2 2425 1843  
Fax + 33 1 34 23 53 48  
Tel. + 49 30 3435 02 10  
Tel. + 39 0362 34 58 11  
Tel. + 971 4810 3295  
service.nl@tencategeo.com  
service.at@tencategeo.com  
service.cz@tencategeo.com  
service.fr@tencategeo.com  
service.de@tencategeo.com  
service.it@tencategeo.com  
service.nme@tencategeo.com

**Poland**  
**Russia | CIS**  
**Scandinavia | Baltics**  
**Spain | Portugal**  
**Switzerland**  
**Turkey**  
**UK | Ireland**

Tel. + 33 1 34 23 53 63  
Tel. + 43 732 6983 0  
Tel. + 31 546 544 811  
Tel. + 34 607 499 962  
Tel. + 49 30 3435 02 10  
Tel. + 43 732 5983 0  
Tel. + 44 1952 588 066  
service.pl@tencategeo.com  
service.ru@tencategeo.com  
geonordic@tencategeo.com  
service.es@tencategeo.com  
service.ch@tencategeo.com  
service.tr@tencategeo.com  
service.uk@tencategeo.com



TenCate Geosynthetics Austria Gesm.b.H, TenCate Geosynthetics France S.A.S and TenCate Geosynthetics Netherlands b.v. are certified for the design, manufacturing and sales of geotextile and geotextile related products.